



Ficha Técnica Technical Information

Muro Cerámico / Ceramic Wall Tile



Link: [Pasta blanca vs. Pasta Roja](#)



Formato / Size:

30 x 60 cm Rectificado / 11,8" x 23,6" Rectified"



| | | | |
|---|--|-------------------------------|----------------|
|  | Espesor / Thickness | 10 mm | |
|  | Separación de boquilla / Grout separation | 2 mm | |
|  | Tono y Textura Mezclado / Mixed Tone and Texture | Alto / High | |
|  | Resistencia al ataque químico / Chemical Resistance | Conforme / In compliance with | A.S.T.M. C650 |
|  | Resistencia a la flexión / Breaking Strength | ≥ 120 kg / 264 lbs | ISO 10545-4 |
|  | Absorción de agua / Water absorption | 15 - 20 % | A.S.T.M. C373 |
|  | MOHS | 5 - 8 | A.S.T.M. C1028 |
|  | Resistencia al shock térmico / Resistance to thermal shock | Conforme / In compliance with | A.S.T.M. C484 |
|  | Resistencia Al Craquel / Resistance To Crazing | Conforme / In compliance with | A.S.T.M. C1026 |
|  | Resistencia a las manchas / Resistance to staining | Conforme / In compliance with | A.S.T.M. C1378 |

Cesantoni S.A. de C.V. certifica que los resultados anteriores fueron obtenidos en análisis de laboratorio elaborado por el departamento de Control de Calidad. Cesantoni certifies that all results were obtained on a laboratory testing by quality control department.